
Technical data sheet Support bracket AS 30

Item number: 6419370





Medium-duty support bracket for infinitely adjustable fastening on IS 8 support. The support bracket can be fastened to both sides of the I support.

The individual clamping lug, including bolt, nut and washer can also be ordered separately under the item no. 6419007.



St

Steel



Hot-dip galvanised

Master data


Item number	6419370
Туре	AS 30 11 FT
Description 1	Support bracket
Description 2	for IS 8 support
Manufacturer	OBO
Dimension	B110mm
Colour	zinc
Material	Steel
Surface	Hot-dip galvanised
Surface standard	DIN EN ISO 1461
Smallest sales unit	1
Unit of quantity	Piece
Weight	30 kg
Weight unit	kg/100 pc.
CO2 Footprint (GWP) Cradle-to- Gate	0,7691 kg CO2e / 1 Piece

Technical data sheet Support bracket AS 30






Dimensions 110 Length 41 mm Width 110 mm Height 60 mm Dimension A 41 mm OBO AS / AW 30/11 Dimension B 110 mm 0 Dimension H 60 mm




Technical data


Version for	Support bracket
F in kN	3 kN
Maintain electrical functions	no
Rustproof steel, pickled	no

Loads



Load diagram, bracket type AS 30





Load curve with bracket lengths in mm