

# Technical data sheet

45° fitting, right, BKRS 100 FS

Item number: 6061908



Cable tray fitting with 45° cut, for creation of bends on walkable cable trays.



|           |                  |
|-----------|------------------|
| <b>St</b> | Steel            |
| <b>FS</b> | Strip galvanized |

## Master data

|                                    |                          |
|------------------------------------|--------------------------|
| Item number                        | 6061908                  |
| Type                               | BKRS 1050 45R FS         |
| Description 1                      | Cable tray BKRS          |
| Description 2                      | mitre right side         |
| Manufacturer                       | OBO                      |
| Dimension                          | 100x500x1000             |
| Colour                             | zinc                     |
| Material                           | Steel                    |
| Surface                            | Strip galvanized         |
| Surface standard                   | DIN EN 10346             |
| Smallest sales unit                | 1                        |
| Unit of quantity                   | Piece                    |
| Weight                             | 794.4 kg                 |
| Weight unit                        | kg/100 pc.               |
| CO2 Footprint (GWP) Cradle-to-Gate | 39,5022 kg COe / 1 Piece |


# Technical data sheet

## 45° fitting, right, BKRS 100 FS

Item number: 6061908



### Dimensions



|                 |          |
|-----------------|----------|
| Length          | 1,000 mm |
| Width           | 500 mm   |
| Height          | 100 mm   |
| Plate thickness | 2 mm     |
| Dimension B     | 500 mm   |
| Dimension H     | 100 mm   |
| Dimension L     | 1,000 mm |

### Technical data

|                                         |                    |
|-----------------------------------------|--------------------|
| Bend (angle)                            | 45°                |
| Connector version                       | Without connectors |
| Type                                    | Bend, rigid        |
| Walkable                                | yes                |
| Maintain electrical functions           | no                 |
| Mounting perforation in base            | yes                |
| NATO hole pattern                       | no                 |
| Change of direction                     | Horizontal         |
| Rustproof steel, pickled                | no                 |
| Side perforation                        | yes                |
| Permitted temperature range, max.       | 120 °C             |
| Permitted temperature range, min.       | -20 °C             |
| Wide-span version                       | no                 |
| Type of connector, cable support system | Screwed            |