

# Technical data sheet

Clamp clip 2056 W-foot, 1-fold, plastic pressure sleeve, FT

Item number: 1187732



Clamp clip with W-foot, plastic pressure sleeve made of polypropylene. For vertical and horizontal mounting of 1 single cable on angle irons with shaft length 40 mm. With 1-start screw thread on pressure sleeve, universal hexagonal screw head WAF10, with slot and cross recess. Suitable for assembly indoors and outdoors. We recommend the use of a counter-sleeve.



|    |                    |
|----|--------------------|
| St | Steel              |
| FT | Hot-dip galvanised |

## Master data

|                                    |                          |
|------------------------------------|--------------------------|
| Item number                        | 1187732                  |
| Type                               | BS-W1-K-40 FT            |
| Description 1                      | Clamp clip 2056          |
| Manufacturer                       | OBO                      |
| Dimension                          | 34-40mm                  |
| Material                           | Steel                    |
| Surface                            | Hot-dip galvanised       |
| Surface standard                   | DIN EN ISO 1461          |
| Smallest sales unit                | 100                      |
| Unit of quantity                   | Piece                    |
| Weight                             | 10 kg                    |
| Weight unit                        | kg/100 pc.               |
| CO2 Footprint (GWP) Cradle-to-Gate | 0,2131 kg CO2e / 1 Piece |


# Technical data sheet

Clamp clip 2056 W-foot, 1-fold, plastic pressure sleeve, FT

Item number: 1187732



## Dimensions



|                  |         |
|------------------|---------|
| Length           | 22.5 mm |
| Width            | 45 mm   |
| Height           | 109 mm  |
| Plate thickness  | 2 mm    |
| Dimension A      | 22.5 mm |
| Dimension B      | 45 mm   |
| Dimension C      | 34 mm   |
| Dimension G (mm) | M6      |
| Dimension H      | 109 mm  |
| Dimension L      | 35 mm   |
| Dimension t      | 2 mm    |

## Technical data

|                               |                |
|-------------------------------|----------------|
| Number of cables/pipes        | 1              |
| For pipe diameter, max.       | 40 mm          |
| For pipe diameter, min.       | 34 mm          |
| Thread                        | M6             |
| Halogen-free                  | yes            |
| Length of external dimensions | 34 mm          |
| Max. Tightening torque        | 3 Nm           |
| With plastic trough           | yes            |
| Mounting type                 | Angle profile  |
| Slot width                    | 10 mm          |
| Clamping range D, max.        | 40 mm          |
| Clamping range D, min.        | 34 mm          |
| Surface addition              | hot galvanised |
| Material addition             | Steel          |
| With counter-trough           | no             |
| Material of trough            | Plastic        |
| Material quality of trough    | Polypropylene  |