Technical data sheet





Stainless steel screw-in anchor for direct mounting without additional anchors in cracked and uncracked concrete and masonry. With round head for universal fastenings in wet rooms and outdoor areas. Torx drive T30.

Construction product tested according to EAD and CE mark, with European Technical Assessment (ETA) and proof of suitability. Load-bearing capacities under fire loads proven up to fire resistance class R120.


VA

Stainless steel, rustproof 1.4401

Master data

| Item no. | 3498274 |
|--------------------------|--------------------------------------|
| Type | MMS+ P 7.5x75 A4 |
| Description 1 | Screw anchor |
| Description 2 | with panhead |
| Dimension | 7,5x75mm |
| Material description | Stainless steel, rustproof 1.4401 |
| Material | Stainless steel, material no. 1.4401 |
| Material symbol | A4 |
| Smallest sales unit (VG) | 50 Piece |
| Weight | 1,90 kg/100 pc. |

Technical data



| Length | 75,00 mm |
|--------------------------|-----------------|
| Dimension L | 75,00 mm |
| Dimension | 7,5x75 mm |
| Anchor/nail/bolt version | Spiral anchor |
| Drill hole diameter | 6,00 mm |
| Anchor length | 75,00 mm |
| Head diameter | 14,50 mm |
| Head shape | Flat round head |
| Head shape | Other |
| Screw system | Torx |
| Screw system | Torx |