Technical data sheet

PYROCOMB® Intube pipe shell, Ø 60 mm

Item number: 7204290



Internally coated pipe shells with click lock. The inner space can be fitted with cables and electrical installation pipes completely. For interior application. CE-labelled, European approved construction product according to ETA-13/0904 and German general type approval. Fire resistance up to 120 minutes.

Closing with 2 foam plugs included in the delivery. The surface seal is created with ${\tt PYROCOAT@ASX}$ coating.

In some applications, the use of metallic tightening straps is prescribed to secure the pipe shells in light-duty partitions. Details can be found in the mounting instructions/approval.



CE

PVC

Polyvinylchloride

Master data

Item number 7204290 Type CTS 06150 Description 1 Pipe shell Description 2 internally coated Manufacturer OBO Dimension 51x150mm		
Description 1 Pipe shell Description 2 internally coated Manufacturer OBO Dimension 51x150mm	Item number	7204290
Description 2 internally coated Manufacturer OBO Dimension 51x150mm	Type	CTS 06150
Manufacturer OBO Dimension 51x150mm	Description 1	Pipe shell
Dimension 51x150mm	Description 2	internally coated
	Manufacturer	OBO
	Dimension	51x150mm
Colour Grey	Colour	Grey
Material Polyvinylchloride	Material	Polyvinylchloride
Smallest sales unit 1	Smallest sales unit	1
Unit of quantity Piece	Unit of quantity	Piece
Weight 17.5 kg	Weight	17.5 kg
Weight unit kg/100 pc.	Weight unit	kg/100 pc.


Technical data sheet

PYROCOMB® Intube pipe shell, Ø 60 mm





Dimensions				
Ĭ	i	A	Length	150 mm
l l	1		Dimension B	60 mm
1	1		Dimension d min.	50.6 mm
1			Dimension L	150 mm
Ī	f			
Į.		20		
Ĭ	Ī			
'	1	_		
		」		



Technical data

Fire protection version	Assembly insulation
Shape	Round
For opening, min.	65 mm
Accessories required	no