

Technical data sheet

XLR connection, 1 module, straight outlet, 3-pin socket, as soldered connection
Item no. 6105216



Multimedia support with one XLR connection socket, straight cable outlet, without labelling panel, 3-pin XLR socket with soldered connection. Support plate with locking fastening, suitable for horizontal and vertical installation in the system environment.


For installation in Rapid 45 device installation ducts, Rapid 80 device installation ducts, service poles and underfloor systems.

PC Polycarbonate

Master data

Item no.	6105216
Type	MTG-X3F L AL1
Description 1	Multimedia support, XLR, 3-pin
Description 2	socket w. soldered connection
Dimension	45x45mm
Colour	Aluminium-painted
Material	Polycarbonate
Material symbol	PC
Smallest sales unit (VG)	1 Piece
Weight	3,00 kg/100 pc.

Technical data



Width	45,00 mm
Height	45,00 mm
Depth	9,00 mm
Dimension	45 x 45 mm
Surface version	Matt
Fastening type	Lock
Labelling panel	With labelling panel
Halogen-free	<input checked="" type="checkbox"/>
Hinged cover	<input type="checkbox"/>
Lamp-wire connector	<input type="checkbox"/>
With printed label	<input type="checkbox"/>
Mit Staubschutz	<input type="checkbox"/>
Protection rating	IP20
Support ring	<input type="checkbox"/>
Transparent	<input type="checkbox"/>
Use	XLR
Strain relief option	<input type="checkbox"/>
Combination	Basic element with central cover plate