

Technical data sheet

Service outlet - Empty chromium version

Item number: 7405595



Round installation unit with floor covering protection frame for direct installation in the connection socket UDL2-120 for indoor use. When closed, the installation unit can be wet-cleaned. The minimum installation depth is 70 mm.

Cover plate and socket of the Modul 45 series should be ordered separately.



Zn Die-cast zinc

Chrome-plated

Master data

| | |
|---------------------|-----------------------------|
| Item number | 7405595 |
| Type | GESRC2 |
| Description 1 | Service outlet |
| Description 2 | with prot. frame, Cr-plated |
| Manufacturer | OBO |
| Dimension | 130x130x64 |
| Material | Die-cast zinc |
| Surface | Chrome-plated |
| Surface standard | |
| Smallest sales unit | 1 |
| Unit of quantity | Piece |
| Weight | 75.2 kg |
| Weight unit | kg/100 pc. |

Technical data sheet

Service outlet - Empty chromium version

Item number: 7405595



Technical data

| | |
|--|----------------|
| Version for | Round |
| Floor covering protection frame | yes |
| Floor care | Wet |
| Suitable for raised floor installation | no |
| Suitable for cavity floor installation | no |
| Suitable for wet care | yes |
| Suitable for underfloor ducts | yes |
| With floor covering recess | no |
| Protection rating (IP) when used | IP20 |
| Protection rating (IP) when unused | IP66 |
| Protection rating IK code | IK10 |
| Opening mechanism | Locking slider |