

Technical data sheet

External corner, for device installation trunking Rapid 80 type GK-70110
Item number: 6274310



External corner for changing the direction of the GK device installation trunking.
Cover must be ordered separately.



PVC Polyvinylchloride

Master data		
Item number	6274310	
Type	GK-A70110RW	
Description 1	External corner	
Manufacturer	OBO	
Dimension	70x110mm	
Colour	Pure white; RAL 9010	
Material	Polyvinylchloride	
Smallest sales unit	1	
Unit of quantity	Piece	
Weight	116 kg	
Weight unit	kg/100 pc.	
CO2 Footprint (GWP) Cradle-to-Gate	2,3155 kg CO2e / 1 Piece	


Technical data sheet

External corner, for device installation trunking Rapid 80 type GK-70110

Item number: 6274310



Dimensions



Length	270 mm
Width	110 mm
Height	70 mm

Technical data

Number of covers	1
Version for	Base
Halogen-free	no
Cable retaining clip	no
Duct connector	no
Cover mounting type	Internal
Mounting perforation in base	yes
Cover width	76.5 mm
Cover width 2	0 mm
Cover width 3	0 mm
Protection rating	IP30
Protective film	yes
Protection rating IK code	IK08
Symmetrical	yes
Permitted temperature range, max.	60 °C
Permitted temperature range, min.	-15 °C
Angle range, max.	90 mm
Angle range, min.	90 mm