## **Technical data sheet**

### Cable carrier troughs, 3-fold, with mounting rail







Cable support brackets for quick and easy routing of cables in areas where common cable support systems cannot be installed due to lack of space. The cable support brackets possess a large load-bearing surface as well as rounded outer edges to protect the cables.

In accordance with DIN VDE 0298-300, a maximum support spacing of 0.8 m should not be exceeded.

 $\epsilon$ 

St

Steel

FT

Hot-dip galvanised

#### Master data

Item number	6006903	
Туре	KTW 100 3 FT	
Description 1	Cable support trough	
Description 2	triple	
Manufacturer	OBO	
Dimension	300x200x123	
Colour	zinc	
Material	Steel	
Surface	Hot-dip galvanised	
Surface standard	DIN EN ISO 1461	
Smallest sales unit	1	
Unit of quantity	Piece	
Weight	168 kg	
Weight unit	kg/100 pc.	
CO2 Footprint (GWP) Cradle-to- Gate	4,6475 kg CO2e / 1 Piece	

## **Technical data sheet**

# Cable carrier troughs, 3-fold, with mounting rail



**Item number: 6006903** 

Dimensions		
	Length	198 mm
	Width	122 mm
	Height	300 mm
	Plate thickness	2 mm
	Dimension L	300 mm
Technical data		
	Number of troughs	3 St.
	Version for	Multiple
	F in kN per trough	0.5 kN
	With fastening material	no
	Adjustable	no