Technical data sheet

Cable carrier troughs, 6-fold, with mounting rail







Cable support brackets for quick and easy routing of cables in areas where common cable support systems cannot be installed due to lack of space. The cable support brackets possess a large load-bearing surface as well as rounded outer edges to protect the cables.

In accordance with DIN VDE 0298-300, a maximum support spacing of 0.8 m should not be exceeded.

CE

St

Steel

FT

Hot-dip galvanised

Master data

Item number	6006906	
Туре	KTW 100 6 FT	
Description 1	Cable support trough	
Description 2	6-way	
Manufacturer	ОВО	
Dimension	600x200x123	
Colour	zinc	
Material	Steel	
Surface	Hot-dip galvanised	
Surface standard	DIN EN ISO 1461	
Smallest sales unit	1	
Unit of quantity	Piece	
Weight	339 kg	
Weight unit	kg/100 pc.	
CO2 Footprint (GWP) Cradle-to- Gate	9,0563 kg CO2e / 1 Piece	

Technical data sheet

Cable carrier troughs, 6-fold, with mounting rail



Item number: 6006906

Dimensions			
	Length	198 mm	
	Width	122 mm	
	Height	600 mm	
	Plate thickness	2 mm	
	Dimension L	600 mm	
Technical data			
	Number of troughs	6 St.	
	Version for	Multiple	
	F in kN per trough	0.5 kN	
	With fastening material	no	
	Adjustable	no	