

# Technical data sheet

## Cable routing trunking MKS 16, trunking width 16

Item number: 6130151



MKS mini trunking for covered cable routing in internal areas.  
Trunking base with base perforation for direct mounting on the wall.  
Base and cover as set.



**PVC** Polyvinylchloride

### Master data

|                                    |                          |
|------------------------------------|--------------------------|
| Item number                        | 6130151                  |
| Type                               | MKS 1616 rws             |
| Description 1                      | Cable trunking           |
| Description 2                      | LE Set 16x16 9010        |
| Manufacturer                       | OBO                      |
| Dimension                          | 2000x16x16               |
| Colour                             | Pure white; RAL 9010     |
| Material                           | Polyvinylchloride        |
| Smallest sales unit                | 112                      |
| Unit of quantity                   | Metre                    |
| Weight                             | 11.4 kg                  |
| Weight unit                        | kg/100 m                 |
| CO2 Footprint (GWP) Cradle-to-Gate | 0,2447 kg CO2e / 1 Meter |

### Dimensions



|        |          |
|--------|----------|
| Length | 2,000 mm |
| Width  | 16 mm    |
| Height | 16 mm    |

# Technical data sheet

Cable routing trunking MKS 16, trunking width 16

Item number: 6130151



## Technical data

|                               |                     |
|-------------------------------|---------------------|
| Number of fixed partitions    | 0                   |
| Fastening type                | Base perforation    |
| Maintain electrical functions | no                  |
| Halogen-free                  | no                  |
| Cable retaining clip          | no                  |
| Duct connector                | no                  |
| Delivery on a roll            | no                  |
| Usable cross-section          | 150 mm <sup>2</sup> |
| Protective film               | no                  |
| Transparent                   | no                  |