
Technical data sheet

Installation frame for combination of 2x and 2x Modul 45® devices

Item number: 7408682



For the installation of a combination of double and double Modul 45 sockets for System 55 service outlets with mounting support for vertical installation of Modul 45 devices. The installation frame is designed for use with 0° sockets for straight connectors (not angled connectors).



(€



Polycarbonate/Acrylnitrile-butadiene-styrene

R/I	aste	 1040
IVI	aste	 ala


Item number	7408682	
Туре	MT45V 2+2	
Description 1	Installation frame	
Description 2	for 2f + 2f Modul 45	
Manufacturer	OBO	
Colour	Graphite black; RAL 9011	
Material	Polycarbonate/Acrylnitrile-butadiene-styrene	
Smallest sales unit	5	
Unit of quantity	Piece	
Weight	0.9 kg	
Weight unit	kg/100 pc.	
CO2 Footprint (GWP) Cradle-to- Gate	0,0613 kg CO2e / 1 Piece	

Technical data sheet

Installation frame for combination of 2x and 2x Modul 45® devices







Technical data Number of installable devices 2 Floor plate no Seal installation option no Suitable for raised floor installatiyes Suitable for screed-flush closed yes underfloor ducts Suitable for screed-covered underfloor ducts yes Suitable for cavity floor installation yes Suitable for underfloor ducts yes Accessory mounting type Lock Strain relief option yes