
Technical data sheet

Installation frame for combination of 3x and 1x Modul 45® devices

Item number: 7408680



For the installation of a combination of triple and single Modul 45 sockets for System 55 service outlets with mounting support for vertical installation of Modul 45 devices. The installation frame is designed for use with 0° sockets for straight connectors (not angled connectors).



(€



Polycarbonate/Acrylnitrile-butadiene-styrene

R/I		ter	٨.	-+-
IVI	as	Lei	u	ala

Item number	7408680		
Туре	MT45V 3+1		
Description 1	Installation frame		
Description 2	for 3f + 1f Modul 45		
Manufacturer	OBO		
Colour	Graphite black; RAL 9011		
Material	Polycarbonate/Acrylnitrile-butadiene-styrene		
Smallest sales unit	5		
Unit of quantity	Piece		
Weight	0.9 kg		
Weight unit	kg/100 pc.		
CO2 Footprint (GWP) Cradle-to- Gate	0,0511 kg CO2e / 1 Piece		

Technical data sheet

Installation frame for combination of 3x and 1x Modul 45® devices







Technical data		
	Number of installable devices	2
	Floor plate	no
	Seal installation option	no
	Suitable for raised floor installation	yes
	Suitable for screed-flush closed underfloor ducts	yes
	Suitable for screed-covered underfloor ducts	yes
	Suitable for cavity floor installation	yes
	Suitable for underfloor ducts	yes
	Accessory mounting type	Lock
	Strain relief option	yes