### **Technical data sheet**

### 0° socket, Denmark, single, IT-encoded

**Item number: 6117203** 



Socket, single 0°, to Danish standard, encoded for IT power circuit, with screw terminals, 2-pin, 16 A 250 V~, with connection terminals to IEC 60884-1. For installation in Rapid 45 trunking, device installation trunking, service poles, underfloor systems and desk boxes.



PC

Polycarbonate

R/A		ter	٨.	-+-
IVI	as	Lei	u	ala

Item number	6117203	
Туре	SKS-DKE0 RW1	
Description 1	Socket, Danish version	
Description 2	for IT power circuit	
Manufacturer	OBO	
Dimension	250V, 10/16A	
Colour	Pure white; RAL 9010	
Material	Polycarbonate	
Smallest sales unit	12	
Unit of quantity	Piece	
Weight	3.05 kg	
Weight unit	kg/100 pc.	
CO2 Footprint (GWP) Cradle-to- Gate	0,0097 kg CO2e / 1 Piece	

### **Technical data sheet**


### 0° socket, Denmark, single, IT-encoded





# 

Width	45 mm
Height	45 mm



#### **Technical data**

Cover	Central plate		
Closable	no		
Number of units	1		
Number of poles	2		
Printed label/coding	Without printing		
Version for	Single 0°		
Surface version	Not applicable		
Version for	Danish norm (earthing pin)		
Ejection mechanism	no		
Fastening type	Lock		
Labelling panel	no		
Operating temperature, max.	40 °C		
Operating temperature, min.	-5 °C		
increased touch protection	no		
Error current protection	no		
For more difficult conditions (according to VDE)	no		
Halogen-free	no		
Hinged cover	no		
Warning light	no		
With on/off switch	no		
With fine-wire fuse	no		
	II.		

# **Technical data sheet**

# 0° socket, Denmark, single, IT-encoded





Technical data		
	With functional lighting	no
	With orientation lighting	no
	Mounting type	Device installation duct
	Nominal voltage	250 V
	Nominal current	16 A
	Protection rating	Other
	Special power supply	Without special power supply
	Socket angle	0°
	Depth	36 mm
	Transparent	no
	Rotated central insert	no
	Surge protection	no