
Technical data sheet Cable tray SKS 60 FS

Item number: 6056105





SKS 60 = heavy-duty cable tray system with 60 mm side height. The cable tray, type SKS, should also be used for the maintenance of electrical function. For additional data, please refer to BSS fire protection systems. Magnetic shield insulation without cover 20 dB, with cover 50 dB.



St

Steel

FS

Strip galvanized

Master data

Item number	6056105
Туре	SKS 610 FS
Description 1	Cable tray SKS
Description 2	perforated, with connector set
Manufacturer	OBO
Dimension	60x100x3000
Material	Steel
Surface	Strip galvanized
Surface standard	DIN EN 10346
Smallest sales unit	3
Unit of quantity	Metre
Weight	239.4 kg
Weight unit	kg/100 m

Technical data sheet Cable tray SKS 60 FS




В

1,968

0,275x1,259





Technical data sheet Cable tray SKS 60 FS

Item number: 6056105




Technical data

Connector version	Supplied connectors
Mounting system fastening type	Floor Ceiling Wall
Walkable	no
Base perforation	7 x 32
Maintain electrical functions	yes
With cover	no
Mounting perforation in base	yes
NATO hole pattern	no
Usable cross-section	58 cm ²
Usable cross-section	5800 mm²
Rustproof steel, pickled	no
Side perforation	yes
Wide-span version	no
Load test type according to IEC 61537	Type II
Type of connector, cable support system	Screwed

Loads

Insertable support spacings, min.	1.5 m
Insertable support spacings, max.	3 m
Support spacing 1.5 m	2.65 kN/m
Support spacing 2.0 m	1.8 kN/m
Support spacing 2.5 m	1.15 kN/m
Support spacing 3.0 m	0.5 kN/m



Load diagram, cable tray, type SKS 60

- Permitted cable tray/ladder load in kN/m without man load
- 2 Support width in m
- Rail bend in mm at permitted kN/m
- Load scheme during testing
- Load curve with cable tray/ladder width in mm
- Strut bend curve according to support width