Technical data sheet

FireBox T250 with plug-in seals, 2 fuse holders

Item number: 7205762





Junction box with two fuse holders and soft plug-in seals. Sufficiently large wiring compartment through diagonally arranged connection unit with completely premounted, high-temperature-resistant ceramic terminals. Green-yellow labelled protective conductor terminal. Fastening on easily accessible external flaps. Approved for cable systems that maintain the electrical function according to DIN 4102 Part 12 with the classes E30, E60 and E90. Ceramic clamps have been tested according to DIN EN 60998-2-1:2004.

Including 2x MMSplus P 6x35 screw ties.









PP

Polypropylene

Master data

| Item number | 7205762 |
|--|--------------------------|
| Туре | T250ED 16A2F |
| Description 1 | Junction box |
| Description 2 | for function maintenance |
| Manufacturer | OBO |
| Dimension | 240x190x95 |
| Colour | Pastel orange; RAL 2003 |
| Material | Polypropylene |
| Smallest sales unit | 1 |
| Unit of quantity | Piece |
| Weight | 113.054 kg |
| Weight unit | kg/100 pc. |
| CO2 Footprint (GWP) Cradle-to- Gate | 3,3005 kg CO2e / 1 Piece |

Technical data sheet

FireBox T250 with plug-in seals, 2 fuse holders



Item number: 7205762



Technical data

270

| Expandable | no |
|-------------------------------|---------------------------|
| Number of terminals | 7 |
| Type of housing penetration | Cuttable stepped membrane |
| Equipment | Teminal |
| Cover | Not transparent |
| Cover fastening | Screwed |
| Entry from rear | no |
| Entries | 9 x M25 |
| | 7 x M32 |
| Explosion-tested version | no |
| Shape | Rectangular |
| Maintain electrical functions | E 90 |
| For Ex zone | Without |
| For Ex zone gas | Without |
| For Ex zone dust | Without |
| Halogen-free | yes |
| Clear internal dimensions | 225x173x86 mm |
| With screening | no |
| with lid | yes |
| Nominal cross-section, max. | 16 mm² |
| Nominal cross-section, min. | 6 mm² |
| Nominal voltage | 660 V |
| Sealable | no |
| Impact-resistant | no |
| Protection rating | IP66 |
| Transparent lid | no |
| Weatherproof | no |
| | |