Technical data sheet

Junction box T100, closed, transparent elevated cover







Closed junction box for the connection of cables and lines indoors and in protected outdoor areas. Rectangular design without entries. Suitable for wall and ceiling mounting and on mounting panels. With the option to fasten inside and to mount via the corner domes. High, transparent cover with quick lock, sealable. Made from halogen-free and UV-resistentant materials.

With hat profile rail.

Junction box according to DIN EN 60670. Flame-resistant to DIN EN 60695/2/11, test temperature 650 °C. Impact resistance IK07 according to DIN EN 50102. Clear internal dimensions: 136x102x74 mm















Polypropylene / polycarbonate

Master data


Item number	2007772
Туре	T 100 OE HD TR
Description 1	Junction box, closed
Description 2	with high transparent cover
Manufacturer	OBO
Dimension	150x116x83
Colour	Light grey; RAL 7035
Material	Polypropylene / polycarbonate
Smallest sales unit	1
Unit of quantity	Piece
Weight	23.65 kg
Weight unit	kg/100 pc.
CO2 Footprint (GWP) Cradle-to- Gate	1,2776 kg CO2e / 1 Piece

Technical data sheet

Junction box T100, closed, transparent elevated cover



Item number: 2007772



Technical data

Expandable	yes	
Type of entry	None	
Type of entry	Cable	
Type of housing penetration	Without	
Measured insulation voltage Vi	500 V	
Equipment	Without	
Cover	Transparent	
Cover fastening	Screwed	
Entry from rear	yes	
Entries	None	
Explosion-tested version	no	
Flame-resistant	acc. to VDE 0471/DIN 695 Part 2-1, test temperature 650°C	
Shape	Rectangular	
Maintain electrical functions	Without	
For Ex zone	Without	
For Ex zone gas	Without	
For Ex zone dust	Without	
Halogen-free	yes	
Clear internal dimensions	136x102x74 mm	
With screening	no	
with lid	yes	
Mounting type	Wall/ceiling mounting	
Nominal voltage	500 V	
Sealable	yes	
Protection rating	IP66	
Protection rating IK code	IK07.	
Permitted temperature range, max.	60 °C	

Technical data sheet

Junction box T100, closed, transparent elevated cover



Item number: 2007772

Technical data	
Permitted temperature range min.	, -5 °C
Transparent lid	no
Weatherproof	no