Technical data sheet

Junction box T160, plug-in seal, elevated cover

Item number: 2007714





Junction box for the connection of cables and lines indoors and in protected outdoor areas. Rectangular design with plug-in seals to the sides and knock-out entries in the bottom. Suitable for wall and ceiling mounting and on mounting panels. With the option to fasten inside and to mount via the corner domes. High, transparent cover with quick lock, sealable. Made from halogen-free and UV-resistant materials.

With hat profile rail.

Junction box according to DIN EN 60670. Flame-resistant to DIN EN 60695/2/11, test temperature 650 $^{\circ}$ C. Impact resistance IK05 according to DIN EN 50102. Clear internal dimensions: 176x135x84 mm





















Polypropylene / polycarbonate

Master data


Item number	2007714
Туре	T 160 HD LGR
Description 1	Junction box
Description 2	with raised cover
Manufacturer	OBO
Dimension	190x150x94
Colour	Light grey; RAL 7035
Material	Polypropylene / polycarbonate
Smallest sales unit	1
Unit of quantity	Piece
Weight	34.18 kg
Weight unit	kg/100 pc.
CO2 Footprint (GWP) Cradle-to- Gate	1,6517 kg CO2e / 1 Piece

Technical data sheet

Junction box T160, plug-in seal, elevated cover



Item number: 2007714



Technical data

Expandable	yes	
No. of entries	12	
Type of entry	Plug-in seal	
Type of entry	Cable	
Type of housing penetration	Miscellaneous	
Measured insulation voltage Vi	500 V	
Equipment	Without	
Cover	Not transparent	
Cover fastening	Screwed	
Entry from rear	yes	
Entries	7xM25	
	5xM32	
Explosion-tested version	no	
Flame-resistant	acc. to VDE 0471/DIN 695 Part 2-1, test temperature 650°C	
Shape	Rectangular	
Maintain electrical functions	Without	
For Ex zone	Without	
For Ex zone gas	Without	
For Ex zone dust	Without	
Fibre-glass reinforced	yes	
Halogen-free	yes	
Clear internal dimensions	176x135x84 mm	
With screening	no	
with lid	yes	
Mounting type	Wall/ceiling mounting	
Nominal voltage	500 V	
Sealable	yes	
Protection rating	IP66	
Protection rating IK code	IK05.	
Permitted temperature range, max.	60 °C	

Technical data sheet





Item number: 2007714

Technical data		
Perm min.	nitted temperature range,	-5 °C
Trans	sparent lid	no
Weat	herproof	no