## **Technical data sheet**

### Junction box T160, with plug-in seal, transparent elevated cover

Item number: 2007754





Junction box for the connection of cables and lines indoors and in protected outdoor areas. Rectangular design with plug-in seals to the sides and knock-out entries in the bottom. Suitable for wall and ceiling mounting and on mounting panels. With the option to fasten inside and to mount via the corner domes. High, transparent cover with quick lock, sealable. Made from halogen-free and UV-resistant materials.

With hat profile rail.

Junction box according to DIN EN 60670. Flame-resistant to DIN EN 60695/2/11, test temperature 650  $^{\circ}$ C. Impact resistance IK05 according to DIN EN 50102. Clear internal dimensions: 176x135x84 mm























Polypropylene / polycarbonate

#### Master data

Item number	2007754
Type	T 160 HD TR
Description 1	Junction box
Description 2	with high transparent cover
Manufacturer	OBO
Dimension	190x150x94
Colour	Light grey; RAL 7035
Material	Polypropylene / polycarbonate
Smallest sales unit	1
Unit of quantity	Piece
Weight	34.18 kg
Weight unit	kg/100 pc.
CO2 Footprint (GWP) Cradle-to- Gate	1,6554 kg CO2e / 1 Piece

# **Technical data sheet**

# Junction box T160, with plug-in seal, transparent elevated cover





# Dimensions 76 76 78 78 79 190

Length	190 mm
Width	150 mm
Height	94 mm

#### Technical data

Expandable	yes
No. of entries	12
Type of entry	Plug-in seal
Type of entry	Cable
Type of housing penetration	Cuttable stepped membrane
Measured insulation voltage Vi	500 V
Equipment	Miscellaneous
Cover	Transparent
Cover fastening	Screwed
Entry from rear	yes
Entries	7xM25
	5xM32
Explosion-tested version	no
Flame-resistant	acc. to VDE 0471/DIN 695 Part 2-1, test temperature 650°C
Shape	Rectangular
Maintain electrical functions	Without
For Ex zone	Without
For Ex zone gas	Without
For Ex zone dust	Without
Fibre-glass reinforced	yes
Halogen-free	yes
Clear internal dimensions	176x135x84 mm
With screening	no
with lid	yes
Mounting type	Wall/ceiling mounting
Nominal voltage	500 V
Sealable	yes
Protection rating	IP66
Protection rating IK code	IK05.
Permitted temperature range, max.	60 °C

# **Technical data sheet**

# Junction box T160, with plug-in seal, transparent elevated cover

**Item number: 2007754** 



Technical data	
Permitte min.	ed temperature range, -5 °C
Transpa	arent lid no
Weathe	erproof no