Technical data sheet

Junction box T 250, plug-in seal

Item number: 2007657





Junction box for the connection of cables and lines indoors and in protected outdoor areas. Rectangular design with plug-in seals to the sides and knock-out entries in the bottom. Suitable for wall and ceiling mounting, on mounting panels and threads in the floor. With the option to fasten inside and to mount via the corner domes. Cover with quick lock, sealable. Made from halogen-free and UV-resistant materials. Junction box according to DIN EN 60670. Flame-resistant to DIN EN 60695/2/11, test temperature 650 °C. Impact resistance IK05 according to DIN EN 50102.





















Polypropylene, fibreglass reinforced

Master data

Item number	2007657	
Туре	T 250 RO-LGR	
Description 1	Junction box	
Description 2	with entries, red cover	
Manufacturer	OBO	
Dimension	240x190x95	
Colour	Grey / red	
Material	Polypropylene, fibreglass reinforced	
Smallest sales unit	1	
Unit of quantity	Piece	
Weight	44.8 kg	
Weight unit	kg/100 pc.	
CO2 Footprint (GWP) Cradle-to- Gate	1,6309 kg CO2e / 1 Piece	

Technical data sheet

Junction box T 250, plug-in seal





| Length | 240 mm | Width | 190 mm | Height | 95 mm |

Technical data

240

=			
Expandable	yes		
No. of entries	16		
Type of entry	Plug-in seal		
Type of entry	Cable		
Type of housing penetration	Cuttable stepped membrane		
Measured insulation voltage Vi	500 V		
Equipment	Without		
Cover	Not transparent		
Cover fastening	Screwed		
Entry from rear	yes		
Entries	9 x M25		
	7 x M32		
Explosion-tested version	no		
Flame-resistant	acc. to VDE 0471/DIN 695 Part 2-1, test temperature 650°C		
Shape	Rectangular		
Maintain electrical functions	Without		
For Ex zone	Without		
For Ex zone gas	Without		
For Ex zone dust	Without		
Fibre-glass reinforced	yes		
Halogen-free	yes		
Clear internal dimensions	225x173x86 mm		
With screening	no		
with lid	yes		
Mounting type	Wall/ceiling mounting		
Nominal cross-section, min.	25 mm²		
Nominal voltage	500 V		
Sealable	yes		
Protection rating	IP66		
Protection rating IK code	IK05.		
Permitted temperature range, max.	00 °C		
Permitted temperature range, min.	-5 °C		

Technical data sheet Junction box T 250, plug-in seal



Item number: 2007657

Technical data		
	Transparent lid	no
	Weatherproof	no