Technical data sheet

Junction box T 350, plug-in seal, terminal strip







Junction box with terminal strip for the connection of cables and lines indoors and in protected outdoor areas. Rectangular design with plug-in seals. Suitable $\,$ for wall and ceiling mounting, on mounting panels and threads in the floor. With the option to fasten inside and to mount via the corner domes. Cover with quick lock, sealable. Made from halogen-free and UV-resistant materials. Junction box according to DIN EN 60670. Flame-resistant to DIN EN 60695/2/11, test temperature 650 °C. Impact resistance IK05 according to DIN EN 50102.























Polypropylene, fibreglass reinforced

Master data

Item number	2007448
Туре	T 350 KL
Description 1	Junction box
Description 2	with terminal strip + entries
Manufacturer	OBO
Dimension	285x201x120
Colour	Light grey; RAL 7035
Material	Polypropylene, fibreglass reinforced
Smallest sales unit	1
Unit of quantity	Piece
Weight	95.7 kg
Weight unit	kg/100 pc.
CO2 Footprint (GWP) Cradle-to- Gate	3,7581 kg CO2e / 1 Piece

Technical data sheet

Junction box T 350, plug-in seal, terminal strip



Item number: 2007448

Dimensions Length Width 201 mm Height 120 mm

Technical data

Expandable	yes		
No. of entries	24		
Number of terminals	5		
Type of entry	Plug-in seal		
Type of entry	Cable		
Type of housing penetration	Cuttable stepped membrane		
Measured insulation voltage Vi	500 V		
Equipment	Terminal		
Cover	Not transparent		
Cover fastening	Screwed		
Entry from rear	yes		
Entries	16 x M32		
	8 x M40		
Explosion-tested version	no		
Flame-resistant	acc. to VDE 0471/DIN 695 Part 2-1, test temperature 650°C		
Shape	Rectangular		
Maintain electrical functions	Without		
For Ex zone	Without		
For Ex zone gas	Without		
For Ex zone dust	Without		
Fibre-glass reinforced	yes		
Halogen-free	yes		
Clear internal dimensions	267x182x110 mm		
With screening	no		
with lid	yes		
Mounting type	Wall/ceiling mounting		
Nominal cross-section, min.	35 mm²		
Nominal voltage	500 V		
Sealable	yes		
Protection rating	IP66		
Protection rating IK code	IK05.		
Permitted temperature range, max.	60 °C		
Permitted temperature range, min.	-5 °C		
Transparent lid	no		

Technical data sheet

Junction box T 350, plug-in seal, terminal strip



Item number: 2007448

Technical data		
	Weatherproof	no