
## **Technical data sheet**

### **Trunking unit with cable outlet M25**

Item no. 7428193





The raised floor trunking can be used for routing cables underneath raised floor panels. Retaining straps permit the self-contacting mounting of separating retainers.

•

St Steel

FS

Strip galvanised


Product text, scope of delivery

Included in the delivery are one trunking base, four trunking covers and eight locking brackets. Two trunking covers have three M25 pipe entry openings. Two trunking covers are completely closed. Separating retainers should be ordered separately.

#### Master data

Item no.	7428193	
Туре	RFT 225 40	
Description 1	Raised floor trunking	
Description 2	with cover	
Dimension	2400x225x40	
Material	Steel	
Material symbol	St	
Surface	Strip galvanised	
Surface to DIN	DIN EN 10346	
Surface symbol	FS	
Weight	1.019,50 kg/100 pc.	

#### **Technical data**



Length	2.400,00 mm
Width	225,00 mm
Height	40,00 mm
Dimension b	225,00 mm
Dimension h	40,00 mm
Number of compartments	3,00 pc.
Plate thickness	1,00 mm
Floor plate	
Seal installation option	
Cover fastening, locking	
Installation opening for on-floor tank	
Decouplable	
For pipe connection	
Suitable for expansion joint	
Suitable for screed-flush closed underfloor ducts	
Suitable for flushfloor, open underfloor duct	

# **Technical data sheet**

## **Trunking unit with cable outlet M25**





Technical data	
Suitable for screed-covered underfloor ducts	
With overhang	
With separating retainer	
With connection opening	
With equipotential bonding	
With screening	
Removable cover	
Schwerlastausführung	
Separating retainer fastening	Lock