

Technical data sheet

UTC3 with 2+1 protective contact sockets

Item number: 7404660



Ready-for-connection UTC3 universal support with halogen-free connection cable. It possesses two pre-installed 33° protective contact sockets in white and one pre-installed 33° protective contact socket in orange of 16 A. Suitable for VL connection cables and device installation units of nominal size 2, 4, R4, 6 and R7.



Master data

Item number	7404660
Type	UTC3 G W2OR1
Description 1	Universal support ConnectGST18
Description 2	double white,single orange
Manufacturer	OBO
Dimension	165x76x45
Smallest sales unit	1
Unit of quantity	Piece
Weight	26.63 kg
Weight unit	kg/100 pc.
CO2 Footprint (GWP) Cradle-to-Gate	1,0038 kg CO2e / 1 Piece

Technical data sheet

UTC3 with 2+1 protective contact sockets


Item number: 7404660



Dimensions



Length	175 mm
Width	76 mm
Height	60 mm



Technical data

Number of connections	2
Number of installable devices	3
Version for	Double pure white/single pure orange
Cable length	300 mm
Line cross-section	2.5 mm ²
Length of the supply cable	0.3 m
Socket combination	Single and double
Plug-in system	GST18
Plug connector system, system-specific	yes
Circuit	2
System length	165 mm
Surge protection	no