## **Technical data sheet**

#### **UTC4** with 3+1 protective contact sockets

**Item number: 7404684** 



Ready-for-connection universal support UTC4 with halogen-free connection cable. It possesses three pre-installed 33° protective contact sockets in pure white and one pre-installed 33° protective contact socket in pure orange of 16 A. Suitable for VL connection cables and device installation units of nominal size R7, R9 and 9.





B 4	4			4_
IVI	aste	or (	าลเ	га

Item number	7404684
Туре	UTC4 G W3OR1
Description 1	Universal support ConnectGST18
Description 2	triple white,single orange
Manufacturer	OBO
Dimension	208x76x45
Smallest sales unit	1
Unit of quantity	Piece
Weight	29.51 kg
Weight unit	kg/100 pc.
CO2 Footprint (GWP) Cradle-to- Gate	1,087 kg CO2e / 1 Piece


# **Technical data sheet**

### **UTC4** with 3+1 protective contact sockets





# Dimensions Length Width 76 mm Height 60 mm



	nica	

Number of connections	2
Number of installable devices	4
Version for	Triple pure white/single pure orange
Cable length	300 mm
Line cross-section	2.5 mm <sup>2</sup>
Length of the supply cable	0.3 m
Socket combination	Single and triple
Plug-in system	GST18
Plug connector system, system- specific	yes
Circuit	2
System length	208 mm
Surge protection	yes