

Technical data sheet

UVS energy distributor with plug connection, normal and special circuit
Item number: 6108016



Energy distributor for heavy current technology with plug connection, equipped and pre-wired.

Input: Two 3-phase circuits using self-locking connectors, 5-pin, type GST18i (connector part).

Output: Twelve self-locking connectors, 3-pin, in white (6x) and black (6x), 16 A, type GST18i (socket part: 2 x L1, 2 x L2, 2 x L3 for each rotary current circuit).

Internal wiring: PVC non-sheathed cable H07V-U2.5.



St Steel

Master data		
Item number	6108016	
Type	UVS-6S6W2SA	
Description 1	Underfloor distributor	
Description 2	with plug connection	
Manufacturer	OBO	
Dimension	160x300x48mm	
Material	Steel	
Smallest sales unit	1	
Unit of quantity	Piece	
Weight	140 kg	
Weight unit	kg/100 pc.	
CO2 Footprint (GWP) Cradle-to-Gate	3,6354 kg CO2e / 1 Piece	


Technical data sheet

UVS energy distributor with plug connection, normal and special circuit

Item number: 6108016



Dimensions



Technical data

Connection type	Plug-in system
No. of outlets	12
Number of input circuits	2
Input	5-pole
Colour of the plug connector system	Black/white
Plug connector system, system-specific	yes