

Technical data sheet

UP Flush-mounted electronic box 66, additional clamping space Item no. 2003726



Flush-mounted electronic box, with additional terminal area, for use in masonry with an installation depth of at least 66 mm.

- With 4 couplable connectors with bayonet lock
- 6 combination pipe entries of Ø 20 and 25 mm
- 8 entries up to Ø 20 mm
- 6 entries up to Ø 14 mm
- 2 entries up to Ø 20 mm in the base
- Partition for different voltages, with break-out openings
- 4 x 3 screw domes

Tested according to DIN EN 60670-1, DIN EN 60670-22 and DIN 49073-1.




PP Polypropylene

Master data

Item no.	2003726
Type	UE 66
Description 1	UP Flush-mount. electronic box
Description 2	with device screws
Available from	01.10.2021
Dimension	Ø60xH66x148
Colour	Jet black
Material	Polypropylene
Material symbol	PP
Smallest sales unit (VG)	10 Piece
Weight	6,15 kg/100 pc.

Technical data



Width	76,00 mm
Height	66,00 mm
Length	148,00 mm
Diameter	60,00 mm
No. of entries	22
Entries	22
Type of entry	NYM cables, data cables and corrugated pipes
Type of housing penetration	Break-out opening
Version for	Single
Shape	Electrics socket
Device fixing	Screws ,
Cover	Without
Cover fastening	Screws ,
Entry from rear	<input checked="" type="checkbox"/>
Flame-resistant	acc. to VDE 0471/IEC 60695-2-11, test temperature 650°C
Shape	Oval
For pipe diameter	20/25 mm
Pipe entries Ø 14 mm	6
Pipe entries Ø 20 mm	10
Combination entries Ø 20 / 25 mm	6
Halogen-free	<input checked="" type="checkbox"/>
Max. conductor cross-section	2,50 mm²
With nail strap	<input type="checkbox"/>
With bolts	<input checked="" type="checkbox"/>
Nominal cross section	1,50 - 2,50 mm²

Technical data sheet





UP Flush-mounted electronic box 66, additional clamping space
Item no. 2003726



Technical data

Rated voltage	400,00 V
Impact-resistant	<input checked="" type="checkbox"/>
Protection rating	IP30
Airtight	<input type="checkbox"/>

Table 1

						
	1,5 mm ²	2,5 mm ²	4 mm ²	1,5 mm ²	2,5 mm ²	4 mm ²
	7	5	4	9	7	6
	21	15	12	27	21	18