

Technical data sheet

UP Flush-mounted electronic box 66, airtight

Item no. 2003727



Flush-mounted electronic box, with additional clamping space and airtight membrane entries, for use in masonry with an installation depth of at least 67 mm.

- With 4 couplable connectors with bayonet lock
- 4 combination pipe entries of Ø 20 and 25 mm
- 4 entries up to Ø 20 mm
- 14 entries up to Ø 11 mm
- 2 entries up to Ø 20 mm in the base
- Partition for different voltages, with break-out openings
- 4 x 3 screw domes

Tested according to DIN EN 60670-1, DIN EN 60670-22 and DIN 49073-1.




PP/TPE Polypropylene / thermoplastic elastomer

Master data

Item no.	2003727
Type	UE 66-L
Description 1	UP Flush-mount. electronic box
Description 2	with device screws, airtight
Available from	01.10.2021
Dimension	Ø60xH67x148
Colour	Jet black / blue-grey
Material	Polypropylene / thermoplastic elastomer
Material symbol	PP/TPE
Smallest sales unit (VG)	10 Piece
Weight	6,60 kg/100 pc.

Technical data



Width	76,00 mm
Height	67,00 mm
Length	148,00 mm
Diameter	61,00 mm
No. of entries	24
Type of entry	NYM cables, data cables and corrugated pipes
Type of housing penetration	Insertion membrane
Version for	Single
Shape	Device connection box
Device fixing	Screws ,
Cover	Without
Cover fastening	Screws ,
Entry from rear	<input checked="" type="checkbox"/>
Flame-resistant	acc. to VDE 0471/IEC 60695-2-11, test temperature 650°C
Shape	Oval
For pipe diameter	20/25 mm
Pipe entries Ø 11 mm	14
Pipe entries Ø 20 mm	6
Combination entries Ø 20 / 25 mm	4
Halogen-free	<input checked="" type="checkbox"/>
With nail strap	<input type="checkbox"/>
With bolts	<input checked="" type="checkbox"/>
Nominal cross section	1,50 - 2,50 mm ²
Rated voltage	400,00 V

Technical data sheet

UP Flush-mounted electronic box 66, airtight

Item no. 2003727



Technical data

Impact-resistant	<input checked="" type="checkbox"/>
Protection rating	IP30
Airtight	<input checked="" type="checkbox"/>

Table 1

	1,5 mm ²	2,5 mm ²	4 mm ²	1,5 mm ²	2,5 mm ²	4 mm ²
	7	5	4	9	7	5
	21	15	12	27	21	18