


# Technical data sheet

## Trunking, type WDK 30030

Item number: 6026818



Trunking cover and base with base perforation.



**PVC** Polyvinylchloride

### Master data

|                                    |                          |
|------------------------------------|--------------------------|
| Item number                        | 6026818                  |
| Type                               | WDK30030GR               |
| Description 1                      | Wall trunking system     |
| Description 2                      | with base perforation    |
| Manufacturer                       | OBO                      |
| Dimension                          | 30x30x2000               |
| Colour                             | Stone grey; RAL 7030     |
| Material                           | Polyvinylchloride        |
| Smallest sales unit                | 40                       |
| Unit of quantity                   | Metre                    |
| Weight                             | 24.9 kg                  |
| Weight unit                        | kg/100 m                 |
| CO2 Footprint (GWP) Cradle-to-Gate | 0,4884 kg CO2e / 1 Meter |


# Technical data sheet

## Trunking, type WDK 30030

Item number: 6026818



### Dimensions



|        |          |
|--------|----------|
| Length | 2,000 mm |
| Width  | 30 mm    |
| Height | 30 mm    |

### Technical data

|                                                                         |                     |
|-------------------------------------------------------------------------|---------------------|
| Number of fixed partitions                                              | 0                   |
| Number of cables NYM 3 x 1.5 mm <sup>2</sup> Ø 10.5 mm (without socket) | 4                   |
| Number of cables NYM 3 x 2.5 mm <sup>2</sup> Ø 11.5 mm (without socket) | 4                   |
| Number of cables NYM 5 x 1.5 mm <sup>2</sup> Ø 12.0 mm (without socket) | 4                   |
| Number of insertable partitions                                         | 0                   |
| Version, cable trunking cover                                           | Loose               |
| Fastening type                                                          | Base perforation    |
| Maintain electrical functions                                           | no                  |
| Halogen-free                                                            | no                  |
| Cable retaining clip                                                    | no                  |
| Duct connector                                                          | no                  |
| Delivery on a roll                                                      | no                  |
| Usable cross-section                                                    | 731 mm <sup>2</sup> |
| Protection rating                                                       | IP30                |
| Protective film                                                         | no                  |
| Protection rating IK code                                               | IK04                |
| Permitted temperature range, max.                                       | 60 °C               |
| Permitted temperature range, min.                                       | -5 °C               |