

Technical data sheet

End piece, trunking type WDK 40060

Item number: 6193444



End piece to close the WDK trunking.  
The end pieces are pushed onto the trunking and kept in place by the spring action.



**PVC** Polyvinylchloride

| Master data                        |                          |  |
|------------------------------------|--------------------------|--|
| Item number                        | 6193444                  |  |
| Type                               | WDK HE40060VW            |  |
| Description 1                      | End piece                |  |
| Manufacturer                       | OBO                      |  |
| Dimension                          | 40x60mm                  |  |
| Colour                             | Traffic white; RAL 9016  |  |
| Material                           | Polyvinylchloride        |  |
| Smallest sales unit                | 10                       |  |
| Unit of quantity                   | Piece                    |  |
| Weight                             | 1.136 kg                 |  |
| Weight unit                        | kg/100 pc.               |  |
| CO2 Footprint (GWP) Cradle-to-Gate | 0,0542 kg CO2e / 1 Piece |  |

# Technical data sheet

End piece, trunking type WDK 40060

Item number: 6193444



## Dimensions



|             |         |
|-------------|---------|
| Length      | 27.5 mm |
| Width       | 60 mm   |
| Height      | 40 mm   |
| Dimension a | 60 mm   |
| Dimension b | 40 mm   |
| Dimension H | 60 mm   |

## Technical data

|                                   |            |
|-----------------------------------|------------|
| Version for                       | Left/right |
| Fastening type                    | Lockable   |
| Maintain electrical functions     | no         |
| Halogen-free                      | no         |
| Protection rating                 | IP30       |
| Protective film                   | no         |
| Protection rating IK code         | IK04       |
| Permitted temperature range, max. | 60 °C      |
| Permitted temperature range, min. | -5 °C      |