

# Technical data sheet

Complete unit, triple, 2x 2 protective contact sockets with control light, 1x data technology support  
Item number: 6109916



Pre-terminated connection unit, Modal net housing, triple, suitable for surface mounting or cavity wall installation.

Connection unit, equipped with:

- 1x double protective contact socket, 33° connection direction, colour: pure white, including glow lamp element as control light.
- 1x double protective contact socket, 33° connection direction, colour: red, including glow lamp element as control light.
- 1x data technology support, type DTG-2C, colour: pure white and 1x blanking cover, type ADP-B, colour: pure white.



PC Polycarbonate

## Master data

Item number	6109916
Type	WGA-K3WRD4 RW
Description 1	Modal net complete unit
Description 2	for surface mounting, triple
Manufacturer	OBO
Dimension	63x130x180mm
Colour	Pure white; RAL 9010
Material	Polycarbonate
Smallest sales unit	1
Unit of quantity	Piece
Weight	40.9 kg
Weight unit	kg/100 pc.
CO2 Footprint (GWP) Cradle-to-Gate	2,4803 kg CO2e / 1 Piece

# Technical data sheet

Complete unit, triple, 2x 2 protective contact sockets with  
control light, 1x data technology support  
Item number: 6109916



## Dimensions

