### **Technical data sheet Junction box X 02**

**Item number: 2005054** 





Junction box for the connection of cables in indoor and outdoor areas. Square design with knock-out entries. Suitable for wall and ceiling mounting with the option to fasten outside, inside or to mount via the corner domes. Particularly impact resistant with IK09. Transparent cover with quick lock, sealable. Made from halogen-free and UV-resistant materials.

Junction box according to DIN EN 60670. Flame-resistant to DIN EN 60695/2/11, test temperature 650°C. Impact resistance IK09 according to DIN EN 50102. Protection rating IP67 according to DIN EN 60529.

























Polycarbonate

R/I	aste	- 4	-
IVI	aste	ΙU	ala

Item number	2005054
Туре	X02 LGR-TR
Description 1	Junction box
Description 2	with transparent lid
Manufacturer	OBO
Dimension	95x95x72
Colour	Grey / transparent
Material	Polycarbonate
Smallest sales unit	1
Unit of quantity	Piece
Weight	17.8 kg
Weight unit	kg/100 pc.
CO2 Footprint (GWP) Cradle-to- Gate	0,7448 kg CO2e / 1 Piece


### **Technical data sheet**

#### Junction box X 02


**Item number: 2005054** 



# Dimensions



Length	95 mm
Width	95 mm
Height	72 mm



#### Technical data

Expandable	ves		
No. of entries	7		
Type of entry	Cuttable stepped membrane		
Type of housing penetration	Pre-marking		
Measured insulation voltage Vi	750 V		
Equipment	Without		
Cover	Not transparent		
Cover fastening	Screwed		
Entry from rear	no		
Entries	7 x Ø20		
Explosion-tested version	no		
Flame-resistant	acc. to VDE 0471/DIN 695 Part 2-1, test temperature 650°C		
Shape	Square		
Fibre-glass reinforced	yes		
Halogen-free	yes		
Clear internal dimensions	85x85x57 mm		
Max. Conductor cross-section	2.5 mm <sup>2</sup>		
With screening	no		
with lid	yes		
Mounting type	Wall/ceiling mounting		
Nominal cross-section, max.	2.5 mm <sup>2</sup>		
Nominal cross-section, min.	1 mm²		
Nominal voltage	750 V		
Sealable	yes		
Impact-resistant	yes		

## Technical data sheet Junction box X 02



**Item number: 2005054** 

Technical data		
	Protection rating	IP67
	Protection rating IK code	IK09
	Permitted temperature range, max.	60 °C
	Permitted temperature range, min.	-5 °C
	Transparent lid	yes
	Weatherproof	yes