Technical data sheet

Junction box X 04 with cable gland

Item number: 2005034





Junction box for the connection of cables and lines indoors and in outdoor areas. Square design with knock-out entries. Suitable for wall and ceiling mounting with the option to fasten outside, inside or to mount via the corner domes. Particularly impact resistant with IK09. Cover with quick lock, sealable. Made from halogenfree and UV-resistant materials.

Including 3 cable glands V-TEC M25 and 3 locknuts.

Junction box according to DIN EN 60670. Flame-resistant to DIN EN 60695/2/11, test temperature 650 $^{\circ}$ C. Impact resistance IK09 according to DIN EN 50102. Protection rating IP67 according to DIN EN 60529.























Polycarbonate

М	as	tei	ď	at	la
		٠	_	•	

Item number	2005034		
Туре	X04 G M25 LGR		
Description 1	Junction box		
Description 2	with 3xV-TEC VM and 3x116		
Manufacturer	OBO		
Dimension	114x114x78		
Colour	Light grey; RAL 7035		
Material	Polycarbonate		
Smallest sales unit	1		
Unit of quantity	Piece		
Weight	31.4 kg		
Weight unit	kg/100 pc.		
CO2 Footprint (GWP) Cradle-to- Gate	1,2617 kg CO2e / 1 Piece		

Technical data sheet

Junction box X 04 with cable gland





33 - 4t- 114

Length	114 mm
Width	114 mm
Height	78 mm

Technical data

Expandable	yes		
No. of entries	7		
Type of entry	Cuttable stepped membrane		
Type of housing penetration	Pre-marking		
Measured insulation voltage Vi	750 V		
Equipment	Miscellaneous		
Cover	Not transparent		
Cover fastening	Screwed		
Entry from rear	no		
Entries	7 x Ø20/25		
Explosion-tested version	no		
Flame-resistant	acc. to VDE 0471/DIN 695 Part 2-1, test temperature 650°C		
Shape	Square		
Fibre-glass reinforced	yes		
Halogen-free	yes		
Clear internal dimensions	102x102x60 mm		
Max. Conductor cross-section	4 mm²		
With screening	no		
with lid	yes		
Mounting type	Wall/ceiling mounting		
Nominal cross-section, max.	4 mm²		
Nominal cross-section, min.	1.5 mm²		
Nominal voltage	750 V		
Sealable	yes		
Impact-resistant	yes		
Protection rating	IP67		
Protection rating IK code	IK09		

Technical data sheet

Junction box X 04 with cable gland

Item number: 2005034



Technical data		
	Permitted temperature range, nax.	60 °C
	Permitted temperature range, nin.	-5 °C
Ti	ransparent lid	no
W	Veatherproof	yes