

Technical data sheet

Bolt tie BZ-U

Art.-Nr. 3498326



Bolt tie BZ for the anchoring of medium-duty to heavy-duty loads, both in cracked and non-cracked concrete. It combines high approved loads with small edge distances and axial spacings.




St	Steel
G	Electrogalvanised

Additional product text, instruction	European Technical Approval ETA-99/0010, including characteristic values under fire exposure to fire resistance R 120. Proof of suitability in the case of seismic impacts, categories C1 and C2. Shock approval by the Federal Office for Civil Protection in Bern, Switzerland.
--------------------------------------	---

Master data

Item no.	3498326
Type	BZ-U 8-30-41/95
Description 1	Wedge anchor BZ-U
Dimension	M8x95mm
Material	Steel
Material symbol	St
Surface	Electrogalvanised
Surface to DIN	DIN EN 12329
Surface symbol	G
Smallest sales unit	50,00 Piece
Weight	4,01 kg/100 pc.

Technical data



Length	95,00 mm
Dimension L	95,00 mm
Version	For knocking in
Anchor/nail/bolt version	Spreading anchor
Drill hole depth	60,00 mm
Drill hole diameter	8,00 mm
Clamping range	30-41 mm
Clamping strength	30,00 mm
Thread	M8
Thread type	Metric
Thread metric	8,00
Permitted load range, tension zone	2,40 kN
Approvals available	☒