Technical data sheet

Device installation trunking Rapid 80, trunking width 130, trunking height 90, asymmetrical ltem no. 6277500





GS device installation trunking for mounting on the wall or on fastening panels. The GS device installation trunking possesses self-contacting locking straps to accept a sheet steel partition. The equipotential bonding between the trunking bases takes place using the trunking coupling. The protective measure and the equipotential bonding is guaranteed between the cover and the base by the self-contacting trunking cover. The real system opening is 76.5 mm. The cover must be ordered separately.

Overlengths up to 3,000 mm for trunking bases and covers as well as other RAL colours can be provided on request. The visible surfaces of the painted device installation trunking are laminated.




St

Steel

Master data

Item no.	6277500
Туре	GS-A90130RW
Description 1	Device installation trunking
Description 2	asymmetrical
Dimension	90x130x2000
Colour	Pure white
RAL number	9010
Material	Steel
Material symbol	St
Smallest sales unit (VG)	2 m
Weight	321,00 kg/100 m

Technical data



Length	2.000,00 mm
Width	130,00 mm
Height	90,00 mm
Number of covers	1
Number of insertable partitions	1
Rear panel version (inner side)	With locking lugs
Rectangular shape	
Fastening type	Screw-on
Base perforation	with base perforation
Cable retaining clip	
Trunking height	90,00 mm
Trunking height	130,00 mm
Duct connector	
Cover mounting type	Internal
Mounting perforation in base	
Usable cross-section	100,50 cm ²
Usable cross-section	10.050,00 mm ²
Cover width	76,5 mm
Cover width 2	0,00 mm
Cover width 3	0,00 mm
Cover supplied	

Technical data sheet

Device installation trunking Rapid 80, trunking width 130, trunking height 90, asymmetrical Item no. 6277500



Technical data	
Protective film	
Symmetrical	