


Technical data sheet

MS4121 mounting rail, slot 22 mm, perforated

Item no. 1122956



Heavy-duty C profile rail for individual installation of support constructions, e.g. for cable trays or as a panel for switchgear cabinets. Can also be used for cable routing, in conjunction with clamp clips with a U foot.




St	Steel
FS	Strip galvanised

Master data

Item no.	1122956
Type	MS4121P0600FS
Description 1	Profile rail
Description 2	perforated, slot 22mm
Dimension	600x41x21
Material	Steel
Material symbol	St
Surface	Strip galvanised
Surface to DIN	DIN EN 10346
Surface symbol	FS
Smallest sales unit (VG)	1 Piece
Weight	105,00 kg/100 pc.

Technical data



Length	600,00 mm
Width	41,00 mm
Height	21,00 mm
Dimension L	600,00 mm
Breakable	☐
lampDimension WxH	41x21 mm
Version	Single profile
Type of perforation	Perforated back
Drill hole spacing, centre	50,00 mm
Suitable for maintaining electrical function	☐
Material thickness	2,00 mm
With perforation	☐
With tothing	☒
Profile shape	C profile
Slot width	22,00 mm
Static value A	
Static value Iy	
Static value Iz	
Static value Wy	
Static value Wz	